

Technical drawing of a mechanical assembly, likely a pump or motor, showing a top view with dimensions and callouts.

Dimensions (mm):


- Overall width: 3452
- Overall height: 1500
- Top section width: 2752
- Top section height: 1102
- Bottom section width: 1500
- Bottom section height: 46
- Bottom section width segments: 600, 1188, 1200, 1082, 1300, 1197
- Bottom section height segments: 1188, 1200, 1082, 1300, 1197
- Bottom section total width: 7164

Callouts and Notes:

- P1, P2, P3, P4, P5, P6, P7, P8, P9, P10, P11, P12: Points of interest or fasteners.
- 13: Section or detail reference.
- 15: Section or detail reference.
- 9: Section or detail reference.
- VOIR / SEE DETAIL B FEUILLE/SHEET 3: Reference to detail B on sheet 3.
- VOIR / SEE DETAIL D FEUILLE/SHEET 3: Reference to detail D on sheet 3.
- VOIR / SEE DETAIL E FEUILLE/SHEET 3: Reference to detail E on sheet 3.
- TOLERANCE ±10: Tolerance specification.

DETAIL SOUPAPE (5) & (9)


1/2" G MALE



DETAIL A
ECHELLE 29:320


—VOIR / SEE DETAIL C
FEUILLE/SHEET 3

TOLERANCE	30RBP610R-----> 720R		DATE	Feuille Sheet 1/5
±10	305A, 305B + OPT 307		08-Mar-22	Indice A
		00DCG000450700		






305B

G
FEUILLE/SHEET 3




TOLERANCE	30RBP610R-----> 720R		DATE	Feuille Sheet 2/5
±10	305A, 305B + OPT 307		08-Mar-22	Indice
		00DCG000450700		A



DETAIL H
ECHELLE 1:8


VUE G
VIEW




DETAIL D
ECHELLE 3:16

DETAIL E
ECHELLE 3:16

TAILLE 610R
SIZE 610R




VICTAULIC 5"



1363

VICTAULIC 5"




599

Ø114.3


Ø139.7

728

827





DETAIL C
ECHELLE 13:320




DETAIL B
ECHELLE 13:160

TOLERANCE	30RBP610R-----> 720R	DATE	08-Mar-22	Feuille Sheet 3/5
±10	305A, 305B + OPT 307			Indice
			00DCG000450700	A






X (mm)	Y (mm)	Z (mm)
3616±115	1005±20	843±15




P1 a P10
P1 to P10




3 TROUS Ø11.0
HOLES

2x PE CLIENTE FILLETTE M8
PE CUSTOMER THREADED M8



STANDARD



TOLERANCE	30RBP610R-----> 720R
±10	305A, 305B + OPT 307

	DATE 08-Mar-22	Feuille Sheet 4/5 Indice
00DCG000450700		A

	ENGLISH	FRANCAIS	DEUTSCH	ESPANOL	ITALIANO
	Cooler water inlet and outlet	Entrée et sortie eau évaporateur	Kaltwasser eintritt und austritt	Entrada y salida agua al evaporador	Entrata e uscita acqua evaporatore
	Cooler air vent	Purge air évaporateur	Kaltwasser entlueftungsventil	Purgador aire evaporador	valvola sfogo aria evaporatore
	Water drain	Purge eau évaporateur	Kaltwasser abfluss	Drenaje agua evaporador	Scarico acqua evaporatore
	NA	NA	NA	NA	NA
	Safety relief valve LP	Soupape de sécurité BP	Verdampfer sichereitsventil LP	Valvula de seguridad LP	Valvola di sicurezza LP
	NA	NA	NA	NA	NA
	NA	NA	NA	NA	NA
	NA	NA	NA	NA	NA
	Safety relief valve HP	Soupape de sécurité HP	Verdampfer sichereitsventil HP	Valvula de seguridad HP	Valvola di sicurezza HP
	NA	NA	NA	NA	NA
	NA	NA	NA	NA	NA
	NA	NA	NA	NA	NA
	Services clearances required	Espace nécessaire à la maintenance	Freiraum für wartung	Espacio necesario para servicio y mantenimiento	Spazio necessario per il servizio
	NA	NA	NA	NA	NA
	Electrical box	Coffret électrique	Schaltschrang	Caja electrica	Pannello elettrico
	Main disconnect switch	Interrupteur général	Haupttrennschalter	Interruptor de desconexion principal	Sezionatore general
	NA	NA	NA	NA	NA
	Total operating weight	Poids total en fonctionnement	Betriebsgewicht	Peso en funcionamiento	Peso in funzionamento
	Inlet water	Entrée eau	Wasser eintritt	Entrada agua	Entrata acqua
	Outlet water	Sortie eau	Wasser austritt	Salida agua	Uscita acqua
	Electrical supply entry	Entrée raccordement électrique	Strom Anschlüsse	Entrada cables electricos	Entrata cavi alimentazione
	Center of gravity	Centre de gravité	Maschinenschwerpunkt	Centro de gravedad	Centro di gravita
	Handling Rigging of the unit: the sizing of the rigging or lifting elements is the responsibility of the installer	Manutention de l'unité Le dimensionnement des éléments de manutention ou de levage sont sous la responsabilité du manutentionnaire	Anheben des geräts Der installateur ist für die dimensionierung der hebeelemente verantwortlich	Sostienimento de la unidad Las dimensiones de los elementos de sostienimento o levantamiento es responsabilidad de instalador	Sollevamento dell'apparechio La responsabilita del dimensionamento degli elementi di sistema di sollevamento e di pertinenza dell'installatore

Техника для климата

Доставляем оборудование по всей России от 3 дней транспортными компаниями. Реализуем проекты в десятках регионов — от Калининграда до Владивостока.

9600+

объектов и поставок

от 1 дня

отгрузка в транспортную компанию

Технические данные файла

Документ: Схема Carrier 30RB/30RBP, чиллеры с воздушным охлаждением: габаритный чертёж
00DCG000450700A, 12.2023

Идентификатор библиотеки: LIB-004090

Исходный файл: carrier-00dgcg000450700a-12-2023-30rb-30rbp-shema.pdf

SHA-256 оригинала: 8054c347a46b1a1efc049837a99ebb4f4f98de36eebdd83b9c4759bfe63be000

Постоянная ссылка: <https://iclim.ru/library/carrier-00dgcg000450700a-12-2023-30rb-30rbp-shema.pdf>

Копия сформирована: 03.10.2026 17:15 UTC