

4-way blow ceiling suspended unit

FUQ-C



Seasonal  Smart



Home leave operation



Draught prevention



Individual flap control



Vertical auto swing

Unique Daikin unit for high rooms with no false ceilings nor free floor space

- › Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- › Can easily be installed in both new and refurbishment projects
- › Refurbishing the room? Flexibility to suit every room layout without changing the location of the unit! Via the wired remote controller you can easily control each flap individually and even close the flaps.
- › Reduced energy consumption thanks to specially developed small tube heat exchanger, DC fan motor and drain pump
- › Optimum comfort guaranteed with automatic air flow adjustment to the required load
- › 5 different discharge angles between 0 and 60° can be programmed via the remote control

FUQ-C + RZQG-L9V1/L(8)Y1



Indoor unit		FUQ	71C	100C	125C
Casing	Colour		Fresh White		
Dimensions	Unit	HeightxWidthxDepth	mm		
Sound power level	Cooling/Heating		198x950x950		
Sound pressure level	Cooling	High/Nom./Low	64/64	65/65	65/65
	Heating	High/Nom./Low	41/38/35	46/42/39	47/43/40
Control systems	Infrared remote control		BRC7C58		
	Wired remote control		BRC1D52 / BRC1E52A/B		





Combination with Seasonal Smart outdoor units ensure high quality, optimal comfort, flexible installation and highest efficiency values.

Efficiency data		FUQ + RZQG	71C + 71L9V1	100C + 100L9V1	125C + 125L9V1	71C + 71L8Y1	100C + 100L8Y1	125C + 125L8Y1
Cooling capacity	Nom.	kW	6.8	9.5	12.0	6.8	9.5	12.0
Heating capacity	Nom.	kW	7.5	10.8	13.5	7.5	10.8	13.5
Power input	Cooling	Nom.	kW	1.68	2.46	3.54	1.68	2.46
	Heating	Nom.	kW	1.84	2.73	3.95	1.84	2.73
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A++			A+		
		Pdesign	kW	6.80	9.50	12.00	6.8	9.5
		SEER		6.50	6.11	5.61	6.5	6.11
		Annual energy consumption	kWh	367	545	749	367	545
	Heating (Average climate)	Energy label	A+			A+		
		Pdesign	kW	7.60	11.30	14.13	7.6	11.3
		SCOP		4.20	4.50	4.44	4.2	4.5
		Annual energy consumption	kWh	2,534	3,516	4,456	2,534	3,516
Nominal efficiency	EER		4.05	3.86	3.39	4.05	3.86	3.39
	COP		4.08	3.95	3.42	4.08	3.95	3.42
	Annual energy consumption	kWh	840	1,230	1,770	840	1,230	1,770
	Energy label	Cooling/Heating	A/A			A/A		

Outdoor unit		RZQG			71L9V1	100L9V1	125L9V1	71L8Y1	100L8Y1	125L8Y1
Dimensions	Unit	HeightxWidthxDepth		mm	990x940x320	1,430x940x320		990x940x320	1,430x940x320	
Sound power level	Cooling			dBA	64	66	67	64	66	67
Sound pressure level	Cooling	Nom.		dBA	48	50	51	48	50	51
	Heating	Nom.		dBA	50	52	53	50	52	53
	Night quiet mode	Level 1		dBA	43	45		43	45	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-15~50					
	Heating	Ambient	Min.~Max.	°CWB	-20~15.5					
Refrigerant	Type/GWP					R-410A/2,087.5				
	Charge	kg/TCO ₂ Eq			2.9/6.1	4.0/8.4		2.9/6.1	4.0/8.4	
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240				3N~/50/380-415	

Contains fluorinated greenhouse gases (1) EER/COP according to Eurovent 2012, for use outside EU only (2) Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPE15-112

02/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

Техника для климата

Доставляем оборудование по всей России от 3 дней транспортными компаниями. Реализуем проекты в десятках регионов — от Калининграда до Владивостока.

9600+

объектов и поставок

от 1 дня

отгрузки в транспортную компанию

Технические данные файла

Документ: Каталог Daikin BRC1D52 — RZQSG125L9V

Идентификатор библиотеки: LIB-002704

Исходный файл: daikin-brc1d52-rzqsg125l9v-katalog.pdf

SHA-256 оригинала: 910d6b59225c28ff7c54bb299c4979bea36d6a59e25c5c0572f2e77016645f00

Постоянная ссылка: <https://iclim.ru/library/daikin-brc1d52-rzqsg125l9v-katalog.pdf>

Копия сформирована: 02.10.2026 09:41 UTC