

Wall mounted unit

FTXP-L + RXP-L



Energy saving during standby mode



Online controller via app



Multi model application

Discreet wall mounted unit providing high efficiency and comfort

- › Whisper quiet
- › Online controller (optional)
- › Ideal for above door installation
- › Bluevolution range: lower environmental impact

- › Seasonal efficiency values up to A++ in cooling and heating
- › Space saving contemporary wall mounted design

FTXP-L + RXP-L




Efficiency data		FTXP + RXP	20L + 20L	25L + 25L	35L + 35L
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80
Power input	Cooling	Min./Nom./Max.	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30
	Heating	Min./Nom./Max.	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29
Space cooling	Energy efficiency class		A++		
	Capacity	Pdesign	kW	2.00	2.50
	SEER			6.79	6.92
	Annual energy consumption		kWh/a	104	127
Space heating (Average climate)	Energy efficiency class		A++		
	Capacity	Pdesign	kW	2.20	2.40
	SCOP/A			4.65	4.61
	Annual energy consumption		kWh/a	662	728
Nominal efficiency	EER			4.02	3.83
	COP			4.77	4.36
	Energy labeling Directive	Cooling/Heating		A/A	

Indoor unit		FTXP	20L	25L	35L
Dimensions	Unit	HeightxWidthxDepth	mm		
Weight	Unit		kg		
Air filter	Type		Removable / washable		
Fan	Air flow rate	Cooling	Silent operation/Low/Medium/High	m³/min	4.4/5.9/7.9 / 9.8
		Heating	Silent operation/Low/Medium/High	m³/min	5.3/6.5/8.4 / 10.3
Sound power level	Cooling			dBA	55
	Heating			dBA	55
Sound pressure level	Cooling	Silent operation/Low/High		dBA	20/25/39
	Heating	Silent operation/Low/High		dBA	21/28/39
Control systems	Infrared remote control		ARC480A11		
	Wired remote control		BRC944B2 / BRC073A1		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

Outdoor unit				RXP	20L	25L	35L
Dimensions	Unit	HeightxWidthxDepth		mm	550x658x275		
Weight	Unit			kg	28		
Sound power level	Cooling			dBA	60		62
	Heating			dBA	61		62
Sound pressure level	Cooling	High		dBA	46		48
	Heating	High		dBA	47		48
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-10~46		
	Heating	Ambient	Min.~Max.	°CWB	-15~18		
Refrigerant	Type				R-32		
	GWP				675.0		
	Charge			kg/TCO2Eq	0.70/0.48		
Piping connections	Liquid	OD		mm	6,35		
	Gas	OD		mm	9.5		
	Piping length	OU - IU	Max.	m	15		
	Additional refrigerant charge			kg/m	0.02 (for piping length exceeding 10m)		
	Level difference	IU - OU	Max.	m	12		
Power supply	Phase/Frequency/Voltage			Hz/V	1~/50/220-240		
Current - 50Hz	Maximum fuse amps (MFA)			A	-		

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPE18-046

01/2018



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Техника для климата

Доставляем оборудование по всей России от 3 дней транспортными компаниями. Реализуем проекты в десятках регионов — от Калининграда до Владивостока.

9600+

объектов и поставок

от 1 дня

отгрузка в транспортную компанию

Технические данные файла

Документ: Каталог Daikin Comfora

Идентификатор библиотеки: LIB-002317

Исходный файл: daikin-comfora-katalog.pdf

SHA-256 оригинала: 5218fe01048ea5266de6ae7360a854268b72274494d32f3aa08750b7ffe1db12

Постоянная ссылка: <https://iclim.ru/library/daikin-comfora-katalog.pdf>

Копия сформирована: 02.10.2026 08:11 UTC