

Pair, Twin, Triple, double twin

RZQ-C



Inverter



Auto cooling-heating
changeover

Packaged system for commercial applications

- › Re-use of existing R-22 or R-407C technology
- › Guarantees operation in heating mode down to -15°C
- › Standard night quiet mode
- › Maximum piping length up to 100m
- › Maximum installation height difference up to 30m
- › Wide range of connectable indoor units

RZQ-C




RZQ200-250C

	FCQG-F					FFQ-C		FDXS-F(9)		FBQ-D					FHQ-C					FUQ-C			FAQ-C		FDQ-C	FNQ-A	
capacity class	50	60	71	100	125	50	60	50	60	50	60	71	100	125	50	60	71	100	125	71	100	125	71	100	125	50	60
RZQ200C	4	3	3	2		4	3	4	3	4	3	3	2		4	3	3	2		3	2		3	2		4	3
RZQ250C		4			2		4		4		4			4		2			2			2			2		4

Outdoor unit				RZQ	200C	250C
Dimensions	Unit	HeightxWidthxDepth	mm		1,680x930x765	
Sound power level	Cooling		dBA		78	
	Heating		dBA		78	
Sound pressure level	Nom.		dBA		57	
Operation range	Cooling	Ambient	Min.~Max.	°CDB	-5.0~46.0	
	Heating	Ambient	Min.~Max.	°CWB	-15.0~15.0	
Refrigerant	Type/Charge/GWP		kg/TCO _{eq}		R-410A/8.3/17.3/2,087.5	R-410A/9.3/19.4/2,087.5
Power supply	Phase/Frequency/Voltage		Hz/V		3N~/50/380-415	

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-127

04/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

Техника для климата

Доставляем оборудование по всей России от 3 дней транспортными компаниями. Реализуем проекты в десятках регионов — от Калининграда до Владивостока.

9600+

объектов и поставок

от 1 дня

отгрузки в транспортную компанию

Технические данные файла

Документ: Каталог Daikin FDQ200B — RZQ250C

Идентификатор библиотеки: LIB-002359

Исходный файл: daikin-fdq200b-rzq250c-katalog.pdf

SHA-256 оригинала: 61d739e55ab41e7300d8a198985a244136c24ec5486f59ce3145d639edc21c6b

Постоянная ссылка: <https://iclim.ru/library/daikin-fdq200b-rzq250c-katalog.pdf>

Копия сформирована: 02.10.2026 09:44 UTC