

Wall mounted unit

FTXZ-N


R-32
**Ururu
Sarara**


3 area intelligent eye


Online controller
via app

Ururu -
humidification

Sarara -
dehumidification


Flash Streamer

Complete climate control with (de)humidification, air purification & ventilation with top efficiencies in heating & cooling

- › SEER + SCOP = A+++ on the entire range
- › Unique combination of humidification, dehumidification, ventilation, air purification and heating & cooling in 1 system
- › 3 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment. Detection is done in 3 directions: left, front and right. If no people are detected, the unit will automatically switch over to the energy-efficient setting

- › No need to clean filters manually
- › Reddot design award winner 2013
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet

FTXZ-N + RXZ-N




Indoor unit		FTXZ	25N	35N	50N
Casing	Colour		White		
Dimensions	Unit	HeightxWidthxDepth	mm		
Sound power level	Cooling/Heating		54/56	57/57	60/59
Sound pressure level	Cooling	High/Nom./Low/Silent operation	38/33/26/19	42/35/27/19	47/38/30/23
	Heating	High/Nom./Low/Silent operation	39/35/28/19	42/36/29/19	44/38/31/24
Control systems	Infrared remote control		ARC477A1		

Efficiency data		FTXZ + RXZ	25N + 25N	35N + 35N	50N + 50N
Cooling capacity	Min./Nom./Max.	kW	0.6/2.5/3.9	0.6/3.5/5.3	0.6/5.0/5.8
Heating capacity	Min./Nom./Max.	kW	0.6/3.6/7.5	0.6/5.0/9.0	0.6/6.3/9.4
Power input	Cooling	Min./Nom./Max.	0.11/0.41/0.88	0.11/0.66/1.33	0.11/1.10/1.60
	Heating	Min./Nom./Max.	0.10/0.62/2.01	0.10/1.00/2.53	0.10/1.41/2.64
Seasonal efficiency (according to EN14825)	Cooling	Energy label	A+++		
		Pdesign	2.50	3.50	5.00
		SEER	9.54	9.00	8.60
		Annual energy consumption	92	136	203
	Heating (Average climate)	Energy label	A+++		
		Pdesign	3.50	4.50	5.60
		SCOP	5.90	5.73	5.50
		Annual energy consumption	831	1,100	1,427
Nominal efficiency	EER		6.10	5.30	4.55
	COP		5.80	5.00	4.47
	Annual energy consumption	kWh	205	330	550
	Energy label	Cooling/Heating	A/A		

Outdoor unit		RXZ	25N	35N	50N
Dimensions	Unit	HeightxWidthxDepth	mm		
Sound power level	Cooling		59	61	63
	Heating		59	61	64
Sound pressure level	Cooling	High	46	48	49
	Heating	High	46	48	50
Operation range	Cooling	Ambient Min.-Max.	°CDB -10~43		
	Heating	Ambient Min.-Max.	°CWB -20~18		
Refrigerant	Type/GWP		R-32/675		
	Charge	kg/TCO ₂ eq	1.34/0.9		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load | Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPE15-021

03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.

Техника для климата

Доставляем оборудование по всей России от 3 дней транспортными компаниями. Реализуем проекты в десятках регионов — от Калининграда до Владивостока.

9600+

объектов и поставок

от 1 дня

отгрузка в транспортную компанию

Технические данные файла

Документ: Каталог Daikin FTXZ25N / RXZ25N — FTXZ50N / RXZ50N с зимним комплектом (-30)

Идентификатор библиотеки: LIB-002373

Исходный файл: daikin-ftxz25n-rxz25n-ftxz50n-rxz50n-s-zimnim-komplektom-30-katalog.pdf

SHA-256 оригинала: bc82b366bc48fefe7deaf85a519f964f138cbf3ce6dba269a9c342f81200d125

Постоянная ссылка:

<https://iclim.ru/library/daikin-ftxz25n-rxz25n-ftxz50n-rxz50n-s-zimnim-komplektom-30-katalog.pdf>

Копия сформирована: 02.10.2026 08:16 UTC